

## 120X120X25 mm

## UA1225-2N Series



- **Motor** : Two-pole shaded pole induction motor
- **Frame** : Aluminum Alloy, Painted black
- **Impeller** : Retardant thermoplastic in black color, rated UL94V-0
- **Speed Range** : ±10%
- **Impedance protected**

### SPECIFICATIONS

Model	Bearing	Nominal Voltage (V)	Frequency (Hz)	Air Flow (CFM)	Static Pressure (inchH <sub>2</sub> O)	Speed (R.P.M.)	Nominal Current (Amp)	Input Power (Watt)	Noise (dBA)	Weight (g)
UA1225H2B-2N	Dual Ball Sleeve	230	50	58	0.150	2300	0.08	15	35	320
			60	66	0.197	2700		17	37	
UA1225M2B-2N			50	47	0.071	1800	0.05	10	30	
		60	60	0.079	2400	12		35		
UA1225H1B-2N		120	50	58	0.150	2300	0.15	15	35	
			60	66	0.197	2700		17	37	
UA1225M1B-2N	50		47	0.071	1800	0.10	10	30		
	60	60	0.079	2400	12		35			

Specifications subject to change without notice

The 9<sup>TH</sup> character of Model No means the bearing code. Please refer to the page "AC FAN PART NUMBER SYSTEM".

