

135X135X38 mm

UA1338-0N Series



- **Motor** : Two-pole shaded pole induction motor
- **Frame** : Aluminum Alloy, Painted black
- **Impeller** : Retardant thermoplastic in black color, rated UL94V-0
- **Speed Range** : $\pm 10\%$
- **Impedance protected**

SPECIFICATIONS

Model	Bearing	Nominal Voltage (V)	Frequency (Hz)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Nominal Current (Amp)	Input Power (Watt)	Noise (dBA)	Weight (g)
UA1338H2B-0N	Dual Ball Sleeve	230	50	115	0.256	2600	0.14	21	43	570
			60	141	0.268	3000			23	
UA1338M2B-0N			50	107	0.169	2400	0.10	14	41	
			60	120	0.201	2700			15	
UA1338L2B-0N			50	90	0.071	2100	0.07	9	39	
			60	107	0.118	2400			10	
UA1338H1B-0N		120	50	115	0.256	2600	0.22	21	43	
			60	141	0.268	3000			23	
UA1338M1B-0N			50	107	0.169	2400	0.18	14	41	
			60	120	0.201	2700			15	
UA1338L1B-0N			50	90	0.071	2100	0.12	9	39	
			60	107	0.118	2400			10	

Specifications subject to change without notice

The 9TH character of Model No means the bearing code. Please refer to the page "AC FAN PART NUMBER SYSTEM".

