

CUSTOMER:神牛

NO.:2020062416

DISTRIBUTOR: 健策
(PE48AA1)

APPROVE SHEET
[Compliance with RoHS]

PRODUCT: DC BRUSHLESS FAN

USER P/N: _____

Parts No.: KF0610H1VM0137JURRB

Printed model number on the stick: KF0610H1LMBR

(SIGNATURE)

JAMICON GROUP
KAIMEI ELECTRONIC CORP.

Tel: +886-2-26981010

Fax: +886-2-26980386



APPROVED	CHECKER	DRAWN
		郝文姣 2020/06/24



JIAN 健策

JIAN 健策
0755-23706799

ECN 變更履歷表

成品料號:	KF0610H1VM0137JURRB	客戶:	健策-神牛
版本	變更內容	日期	
A0	初版	2020/06/24	

JIAN  健策

JIAN  健策
 0755—23706799



1. MECHANICAL:

1-01	Dimension	Dimension of fan shall be shown in the outline styling drawing attached.
1-02	Motor	Four-pole motor.
1-03	Frame	Plastic material UL 94V-0.(P.B.T)
1-04	Impeller	Plastic material UL 94V-0.(P.B.T)
1-05	Free drop shock	In minute package condition, the fan should withstand each one drop of three faces from 30cm distance height onto 10 mm thickness of wooden board.

2.ELECTRICAL:25°C/65%RH

2-01	Rated current	Rated current shall be measured after 30 minutes continuous rotation at rated voltage.
2-02	Start voltage	The voltage that enable to start the fan by sudden switch on.
2-03	Rated Speed	Rated speed shall be measured after 30 minutes continuous rotation at rated voltage.
2-04	Input Power	Input power shall be measured after 30 minutes continuous rotation at rated voltage.
2-05	Lock Current	Locked current shall be measured Within one minute at rotor locked, after 30 minutes continuous rotation at rated voltage in clear air.
2-06	Insulation resistance	More than 10M ohm at 500 V.D.C between lead and housing.
2-07	Dielectric strength	Measured 5 mA(max) trip current at 700 V.A.C for 3 sec. between lead and housing.
2-08	Locked motor protection	Designed to meet UL, CUL and TUV.

DO NOT use power or ground PWM to control the fan speed.If the fan speed needs to be adjusted,please contact JAMICON to customize the product design for your application

JIAN 健策


0755—23706799

微信扫码
咨询工程师



3.CHARACTERISTICS:

3-01	Air Flow & Static Pressure	The air flow data and static pressures should be determined in accordance with AMCA standard or DIN 24163 specification in a double- chamber testing with intake-side measurement.
3-02	Noise level	The measurement of noise level is carried out with reference to DIN 45635 in an echoic chamber with the microphone positioned 1 M from the air intake. Testing fan shall be hung in clean air.



4.ENVIRONMENTAL:

4-01	Operating temperature	-10°C to 70°C (ordinary humidity)
4-02	Storage Temperature	-40°C to 70°C (ordinary humidity)
4-03	Humidity	After 96 hrs, 95% RH 40±2°C per MIL-STD-202F method 103B, Humidity test , The measured data of insulation resistance & dielectric strength should meet the specification listed in attach.
4-04	Thermal Shock	After thermal shock test per MIL-STD-202F method 107D, Condition D, The measured data of insulation resistance & dielectric strength should the specification

JIAN 健策

0755—23706799

微信扫码
咨询工程师



5.DATA-SHEET:

PARTS NO.: KF0610H1VM0137JURRB

SAP NO.: K0610H1VM0137JURB

5-1. SPECIFICATION:

NO.	ITEM	SPECIFICATION	UNIT	CONDITION
5-1-01	Dimension	60*60*10	mm	-----
5-1-02	Bearing	HTLS	-----	-----
5-1-03	Rated Voltage	12	VDC	-----
5-1-04	Operating Voltage	7.0~13.8	VDC	MAX 13.8V.
5-1-05	Start Voltage	7.0	VDC	On/off test max.
5-1-06	Speed	1800	R.P.M	±15%,At rated Voltage
5-1-07	Input Current	0.08	Amp	At rated Voltage
5-1-08	Input Power	0.96	Watt	At rated Voltage
5-1-09	Nominal Power	1.6	Watt	At rated Voltage
5-1-10	Air Flow	6.24	CFM	At 0 static Pressure of rated speed
5-1-11	Static Pressure	0.022	inchH ₂ O	At 0 air flow of rated speed
5-1-12	Noise	16.0	dBA	At rated speed
5-1-13	Life Expectancy(L10)	70,000	Hours	At 40°C Bearing
5-1-14	Motor protection	Electronic protected		
5-1-15	Polarity protection	It will not damage the fan while reverse input.		
5-1-16	Auto Restart	YES	-----	-----
5-1-17	Speed Signal output	YES(1)	-----	-----
5-1-18	Alarm Signal output	NO	-----	-----
5-1-19	Rotation direction	From the label side	-----	Clockwise
5-1-20	Weight	27	Gram	Per each piece
5-1-21	Safety Certificate	UL,CUL,TUV,CE	-----	-----

5-2. LEAD WIRE:


NO.	ITEM	CONDITION			
5-2-01	AWG NO. & Authorize	26AWG, UL1007 (The end of wire with tin as drawing)			
5-2-02	Color	—	+	Speed	
		Black	Red	White	
5-2-03	Line Length	100±10 mm			
5-2-04	Connector	Notes as: Not available			
5-2-05	Tube	NO			

JIAN 健策

0755—23706799

微信扫码
咨询工程师





JIAN 健策


JIAN 健策
 0755—23706799



KAIMEI ELECTRONIC CORP.

風扇噪音性能測試報告 (The Test Report of Fan Noise)

風扇型號(Sample Type) KF0610-01
 基本規格(roperties) DC 12 V 11 葉 4 極
 測試日期(Test Date) 2012 年 9 月 19 日
 測試編號(Tset No.) 216
 測試設備(Test Equip) B&K 2236



Fulfil : IEC 651-1979 TYPE1 | IEC 804-1985 TYPE 1
 ANSI S1.4-1983 TYPE S1 ANSI S1.43-199X TYPE 1

測試條件(Test Conditions)


輸入電壓(Input Voltage) 12 V Hz
 量測時間(Measuring Time) 20 Sec
 麥克風距離(Mic. Distance) 100 cm
 麥克風角度(Mic. Angle) 180°
 頻域加權(Freq. Weighting) A
 時域加權(Time Weighting) SLOW
 背景噪音(Background Noise) 15.0 dB(A)
 溫度(Temperature) 35.5 °C
 相對濕度(Relative Humidity) 68.0 %

測試結果(Test Results)

電壓(Passing Voltage)
 電流(Electric Current)
 消耗功率(Power Dissipation)
 轉速(Rotation Speed) 1800 RPM
 均能聲壓位準(Time-averaged SPL · Leq) (依據CNS 8753)
 最大聲壓位準(MaxL) 14.48 dB(A)
 最小聲壓位準(MinL) 16.40 dB(A)
 量測點(At Meas. Point) 16.00 dB(A)
 1米處(At 1m Point) 16.00 dB(A)

聲壓位準頻譜圖(Sound Pressure Level Octave-Band Spectrum)

頻率(Hz)	31.5	63	125	250	500	1k	2k	4k	8k
dB(A)	7.8	12.6	7.6	0.0	18.3	0.0	0.0	0.0	22.9



簽核人員: _____


操作人員: 周 坤 翬
Chou, Kun-hui

JIAN 健策
 0755—23706799

系統開發(Developer)工業技術研究院機械工業研究所(MIRL/TTRI)



A B C D E F G H



Date code
 XX X XX
 Date
 Month
 Year

SCALE	PRODUCT	UNIT
	APPEARANCE OF FAN	mm
SAP NO.:	K0610H1VM0137JURB	
PARTS NO.:	KF0610H1VM0137JURRB	


REV.	DESCRIPTION	DESIGN	DATE
0		郝文蛟	2020/06/24

JAMICON
 凯美电机有限公司
 KAMEI ELECTRONIC CORP.



Auto restart /Tachometer signal (A)

Diagram:



Where
Rated Voltage:5V
Vcc:7V max

Where
Rated Voltage:12V
Vcc:16V max

Where
Rated Voltage:24V
Vcc:28V max

Where
Rated Voltage:48V
Vcc:60V max

Please select R so that $I_c < 10 \text{ mA}$

Type of signal

