

CUSTOMER: 健策

NO.: SZ1670008

DISTRIBUTOR:
(PE48AA1)

APPROVE SHEET

[Compliance with RoHS]

PRODUCT: DC BRUSHLESS FAN

USER P/N : _____

Parts No.: KF0510B1HR018CG58R

Printed model number on the stick: KF0510B1HR- R

(SIGNATURE)

Empty box for signature.

JAMICON GROUP
JINMICON ELECTRONIC(SHENZHEN)CO.,LTD
TEL:0755-2812 9962
FAX;0755-2812 9995



APPROVED	CHECKED	DRAWN
		郝文姣 2016/07/07



JIAN 健策
8755-23706799

1. MECHANICAL:

1-01	Dimension	Dimension of fan shall be shown in the outline styling drawing attached.
1-02	Motor	Four-pole motor.
1-03	Frame	Plastic material UL 94V-0.
1-04	Impeller	Plastic material UL 94V-0.
1-05	Free drop shock	In minute package condition, the fan should withstand each one drop of three faces from 30cm distance height onto 10 mm thickness of wooden board.

2.ELECTRICAL:

2-01	Rated current	Rated current shall be measured after 30 minutes continuous rotation at rated voltage.
2-02	Start voltage	The voltage that enable to start the fan by sudden switch on.
2-03	Rated Speed	Rated speed shall be measured after 30 minutes continuous rotation at rated voltage.
2-04	Input Power	Input power shall be measured after 30 minutes continuous rotation at rated voltage.
2-05	Lock Current	Locked current shall be measured Within one minute at rotor locked, after 30 minutes continuous rotation at rated voltage in clear air.
2-06	Insulation resistance	More than 10M ohm at 500 V.D.C between lead and housing.
2-07	Dielectric strength	Measured 5 mA(max) trip current at 700 V.A.C for 3 sec. between lead and housing.
2-08	Locked motor protection	Designed to meet UL, CUL and TUV.
2-09	DO NOT use power or ground PWM to control the fan speed.If the fan speed needs to be adjusted,please contact JAMICON to customize the product design for your application	

JIAN 健策


0755—23706799

微信扫码
咨询工程师



3.CHARACTERISTICS:

3-01	Air Flow & Static Pressure	The air flow data and static pressures should be determined in accordance with AMCA standard or DIN 24163 specification in a double- chamber testing with intake-side measurement.
3-02	Noise level	The measurement of noise level is carried out with reference to DIN 45635 in an echoic chamber with the microphone positioned 1 M from the air intake. Testing fan shall be hung in clean air.



4.ENVIRONMENTAL:

4-01	Operating temperature	-10°C to 70°C (ordinary humidity)
4-02	Storage Temperature	-40°C to 70°C (ordinary humidity)
4-03	Humidity	After 96 hrs, 95% RH 40±2°C per MIL-STD-202F method 103B, Humidity test , The measured data of insulation resistance & dielectric strength should meet the specification listed in attach.
4-04	Thermal Shock	After thermal shock test per MIL-STD-202F method 107D, Condition D, The measured data of insulation resistance & dielectric strength should the specification

JIAN策 健策

0755—23706799

微信扫码
咨询工程师



5.DATA-SHEET:

MODEL: KF0510B1HR018CG58R

5-1. SPECIFICATION:

NO.	ITEM	SPECIFICATION	UNIT	CONDITION
5-1-01	Dimension	50*50*10	mm	-----
5-1-02	Bearing	Dual Ball	-----	-----
5-1-03	Rated Voltage	12	VDC	-----
5-1-04	Operating Voltage	7.0 ~ 13.8	VDC	MAX. 13.8V
5-1-05	Start Voltage	7.0	VDC	On/off test max.
5-1-06	Speed	5200	R.P.M	±10%, At rated Voltage
5-1-07	Input Current	0.11	Amp	At rated Voltage
5-1-08	Input Power	1.32	Watt	At rated Voltage
5-1-09	Nominal Power	1.6	Watt	At rated Voltage
5-1-10	Air Flow	13.04	CFM	At 0 static Pressure of rated speed
5-1-11	Static Pressure	0.138	inchH ₂ O	At 0 air flow of rated speed
5-1-12	Noise	29.0	dBA	At rated speed
5-1-13	Life Expectancy(L10)	75,000	Hours	At 40°C (Bearing)
5-1-14	Motor protection	Electronic protected		
5-1-15	Polarity protection	It will not damage the fan while reverse input.		
5-1-16	Auto Restart	YES	-----	-----
5-1-17	Speed Signal output	NO	-----	-----
5-1-18	Alarm Signal output	NO	-----	-----
5-1-19	Rotation direction	From the label side	-----	Clockwise
5-1-20	Weight	17	Gram	Per each piece
5-1-21	Safety Certificate	UL, CUL, TUV, CE	-----	-----

5-2. LEAD WIRE:

NO.	ITEM	SPECIFICATION			
5-2-01	AWG NO. & Authorize	26AWG, UL1007(Twist wire)			
5-2-02	Color	—		+	
		Black	Blank	Red	
5-2-03	Line Length	110±5 mm			
5-2-04	Connector	Notes as: Pitch: 2.5 mm Housing: JST XHP-3 compatible parts.			
5-2-05	Tube	白色纖維套管 φ 2.5*100mm			


JIAN 健策

0755—23706799

微信扫码
咨询工程师



JAMICON FAN PERFORMANCE CURVES



JIAN 健策

JIAN 健策

0755—23706799

微信扫码
咨询工程师



KAIMEI ELECTRONIC CORP.

風扇振動噪音性能測試報告


(The Test Report of Fan Vibration and Noise)

風扇型號(Sample Type): KF0510-01
 基本規格(Properties): DC 12V 7葉 4極 5200RPM

測試日期(Test Date): 2005/5/4 AM 10:36:41
 測試編號(Test No.): (1)



測試條件(Test Conditions)

輸入電壓(Input Voltage): 12 V
 量測時間(Measuring Time): 20 sec
 麥克風距離(Mic. Distance): 100 cm
 麥克風角度(Mic. Angle): 180°
 頻域加權(Freq. Weighting): A
 時域加權(Time Weighting): SLOW
 背景噪音(Background Noise): 15.0 dB(A)
 溫度(Temperature): ℃
 相對濕度(Relative Humidity): %



測試結果(Test Results)

電壓(Passing Voltage):
 電流(Electric Current):
 消耗功率(Power Dissipation):
 轉速(Rotation Speed): 5209 RPM
 振動量(Vibration Level) (依據 ISO 2372)
 振動速度(Vib. Velocity): 1.86 mm/sec RMS
 均能聲壓位準(Time-averaged SPL, Leq) (依據 CNS 8753)
 量測點(At Meas. Point): 29.2 dB(A)
 1米處(At 1m Point): 29.0 dB(A)
 最大聲壓位準(MaxL): 29.9 dB(A)
 最小聲壓位準(MinL): 27.1 dB(A)




簽核人員: _____

操作員: 簽章: **JIAN 健策**

系統開發(Developer): 工業技術研究院 機械工業研究所(MTRI/ITRI)

2005/5/4 AM 11:04:51 列印
 0755-23706799





SCALE	PRODUCT	UNIT
	APPEARANCE OF FAN	mm
DWG. NO:	KF0510B1HR018CG58R	
REV.	0	
DESIGN	DATE	
DESCRIPTION	2016/07/08	
	郝文斌	

JAMICON
凯美电机有限公司
KAMEI ELECTRONIC CORP.


KAMEI ELECTRONIC CORP.



健策
0755-23706799

Auto-restart

Fan motor speed



JIAN 健策

JIAN 健策
0755—23706799

微信扫码
咨询工程师

