

92X92X25 mm

DF0925-33 Series

- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : ±10%



SPECIFICATIONS											
Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Power (Watt)	Noise (dBA)	Weight (g)
DF0925-1UR	B S H F	12	10.2~13.8	74.92	0.276	4200	0.60	7.20	7.20	38.0	90
DF0925-1SR				68.04	0.235	3800	0.40	4.80	4.80	28.0	
DF0925-1HR				46.86	0.172	3000	0.24	2.88	2.88	25.2	
DF0925-1LR				35.28	0.124	2200	0.18	2.16	2.16	22.0	
DF0925-2UR		24	20.4~27.6	74.92	0.276	4200	0.30	7.20	7.20	38.0	
DF0925-2SR				68.04	0.235	3800	0.18	4.32	4.32	28.0	
DF0925-2HR				46.86	0.172	3000	0.15	3.60	3.60	25.2	
DF0925-2LR				35.28	0.124	2200	0.12	2.88	2.88	22.0	

Specifications subject to change without notice

The 7TH character of Model No means the bearing code. Please refer to the page "PART NUMBER SYSTEM".
Please contact us for detail if your request bearing system is not shown in the above list.

JAMICON FAN PERFORMANCE CURVES

