

120X120X38 mm

UA1238-4N Series



- **Motor** : Two-pole shaded pole induction motor
- **Frame** : Aluminum Alloy, Painted black
- **Impeller** : Retardant thermoplastic in black color, rated UL94V-0
- **Speed Range** : $\pm 10\%$
- **Impedance protected**

SPECIFICATIONS

Model	Bearing	Nominal Voltage (V)	Frequency (Hz)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Nominal Current (Amp)	Input Power (Watt)	Noise (dBA)	Weight (g)
UA1238H2B-4N	Dual Ball Sleeve	230	50	98	0.287	2600	0.14	21	40	560
			60	112	0.362	3000		23	45	
UA1238M2B-4N			50	90	0.236	2400	0.12	14	39	
			60	100	0.283	2700		15	42	
UA1238L2B-4N			50	78	0.142	2100	0.10	9	25	
			60	90	0.157	2400		10	39	
UA1238H1B-4N		120	50	98	0.287	2600	0.22	21	42	
			60	112	0.362	3000		23	46	
UA1238M1B-4N			50	90	0.236	2400	0.15	14	39	
			60	100	0.283	2700		15	42	
UA1238L1B-4N			50	78	0.142	2100	0.10	9	35	
			60	90	0.157	2400		10	39	

Specifications subject to change without notice

The 9TH character of Model No means the bearing code. Please refer to the page "AC FAN PART NUMBER SYSTEM".

